

09-12-00

Approved for use through 09/30/00, OMB 0651-0032

A +

Please type a plus sign inside this box ☐

PTO/SB/05 (12/97)

UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket No.

13325 0032

Total Pages

18

First Named Inventor or Application Identifier

John K. Schneider et al.

Express Mail Label No.

EK522130920US

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents

ADDRESS TO: Assistant Commissioner for Patents
Box Patent Application
Washington, D.C. 20231

1. ☒ Fee Transmittal Form
(Submit an original, and a duplicate for fee processing)
2. ☒ Specification [Total Pages / 15 /]
(preferred arrangement set forth below)
 - Descriptive title of the Invention
 - Cross References to Related Applications
 - Statement Regarding Fed sponsored R&D
 - Reference to Microfiche Appendix
 - Background of the Invention
 - Brief Summary of the Invention
 - Brief Description of the Drawings (if filed)
 - Detailed Description
 - Claim(s)
 - Abstract of the Disclosure
3. ☒ Drawing(s) (35 USC 113) [Total Sheets / 3 /]
4. ☐ Oath or Declaration [Total Pages / /]
 - a. ☐ Newly executed (original or copy)
 - b. ☐ Copy from a prior application (37 CFR 1.63(d))
(for continuation/divisional with Box 17 completed)
[Note Box 5 below]
 - i. ☐ DELETION OF INVENTOR(S)
Signed statement attached deleting inventor(s) named
in the prior application, see 37 CFR 1.63(d)(2) and
1.33(b).
5. ☐ Incorporation By Reference (useable if Box 4b is checked)
The entire disclosure of the prior application, from
which a copy of the oath or declaration is supplied
under Box 4b, is considered as being part of the
disclosure of the accompanying application and is
hereby incorporated by reference therein.

6. ☐ Microfiche Computer Program (Appendix)
7. Nucleotide and/or Amino Acid Sequence Submission
(if applicable, all necessary)
 - a. ☐ Computer Readable Copy
 - b. ☐ Paper Copy (identical to computer copy)
 - c. ☐ Statement verifying identity of above copies.

ACCOMPANYING APPLICATION PARTS

8. ☐ Assignment Papers (cover sheet & document(s))
9. ☐ 37 CFR 3.73(b) Statement ☐ Power of Attorney
(when there is an assignee)
10. ☐ English Translation Document (if applicable)
11. ☐ Information Disclosure ☐ Copies of IDS
Statement (IDS)/PTO-1449 Citations
12. ☐ Preliminary Amendment
13. ☒ Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)
14. ☒ Small Entity ☐ Statement filed in prior application,
Statement(s) Status still proper and desired
15. ☐ Certified Copy of Priority Document(s)
(if foreign priority is claimed)
16. ☒ Other: fee transmittal and check for \$345.00

17. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of the prior application No: /

18. CORRESPONDENCE ADDRESS

NAME	Martin G. Linihan, Esq.				
	Hodgson, Russ, Andrews, Woods & Goodyear, LLP				
ADDRESS	One M&T Plaza, Suite 2000				
CITY	Buffalo	STATE	New York	ZIP CODE	14203-2391
COUNTRY	United States of America	TELEPHONE	(716) 856-4000	FAX	(716) 849-0349

"Express Mail" Mailing Label Number EK522130920US

Date of Deposit September 11, 2000

I hereby Certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231.

Martin G. Linihan
Name

Signature

T-418 P 05/06 F-734

Docket Number
13325.0032

Date September 11, 2000

MOBILE FINGERPRINT SCANNER AND DOCKING STATION

Cross-Reference To A Related Application

5 Applicants hereby claim priority based on
Provisional Application No. 60/153,182 filed on
September 10, 1999 and entitled "Mobile Fingerprint
Scanner And Docking Station" which is incorporated
hereby by reference.

Background of the Invention

15 Inkless fingerprint scanners, also known as live
scan fingerprint readers or biometric devices, have been
widely used for many years. These systems obtain an
image of the fingerprint without the use of inks. Once
an image is acquired, it is then processed and an
identification or verification of the individual's
identity is made.

20 Many different techniques have been used to obtain
an image of the finger including optical scanners,
thermal scanners, capacitive scanners, E-field sensors,
ultrasonic scanners, and many more. Each uses a
different modality or technique to image the same
25 physical characteristic; the ridge structure of the
finger.

In use of such scanners in law enforcement and
other applications it would be highly desirable to
provide a mobile or portable scanner which can be hand
30 carried easily for convenient use at various physical
locations. It would also be highly desirable to provide
the capability of interfacing with such a scanner at one
or more physical locations for such operations as
downloading fingerprint images and other information

stored in the scanner, scanner battery charging and scanner diagnosis.

5

Summary of the Invention

10 The present invention provides a system including a mobile or portable fingerprint scanner and one or more docking stations adapted to operatively receive the scanner. The scanner can be hand carried to various locations for obtaining fingerprint images and other information such as images from bar code scanning. The scanner is battery operated and has the capacity of storing a number of such images. The docking station is
15 in the form of a receptacle into which the scanner is inserted after obtaining one or more images. While the scanner is operatively received in the docking station, the image(s) stored in the scanner are download via a connection to a personal computer or the like, the
20 scanner battery is recharged and the docking station performs various diagnostic operations on the scanner before it is withdrawn from the docking station for further use. In a typical law enforcement situation, the docking station is located within the law
25 enforcement vehicle and the scanner can be used by law enforcement personnel at locations remote from the vehicle. In a typical security situation, a single scanner is carried by the security officer and a docking station is located at each checkpoint or location where
30 the officer is to perform an inspection. Each bay station has a unique identification and there is bi-directional exchange of information between the scanner and the bay station so that the identity of the security

officer can be confirmed and a record of the inspections is made which can be monitored at any time.

The foregoing and additional advantages and characterizing features of the present invention will become clearly apparent upon a reading of the ensuing detailed description together with the included drawing. The following detailed description of the invention, when read in conjunction with the accompanying drawings, is in such full, clear, concise and exact terms as to enable any person skilled in the art to which it pertains, or with which it is most nearly connected, to make and use the invention.

Brief Description Of The Drawing Figures

Fig. 1 is a diagrammatic view of the mobile fingerprint scanner and docking station according to the present invention;

Fig. 2 is a schematic diagram further illustrating the mobile fingerprint scanner and docking station according to the present invention; and

Fig. 3 is a schematic diagram illustrating application of the mobile fingerprint scanner and docking station of the present invention in a security system.

Detailed Description Of The Illustrated Embodiments

Referring first to Figs. 1 and 2 there is shown and described a system 10 according to the present invention including a mobile or portable fingerprint scanner 12 and a docking station 14 adapted to operatively receive the scanner. The scanner 12 can be hand carried to various locations for obtaining fingerprint images and

other information such as images from bar code scanning. The scanner 12 is battery operated and has the capability of storing a number of such images. The scanner 12 can be of various types including, but not limited to, ultrasonic, optical, capacitance, E-field and thermal/infrared. By way of example, the mobile scanner 12 can be an ultrasonic scanner of the type shown in United States Patent No. 5,647,364 issued July 15, 1997, the disclosure of which is hereby incorporated by reference. Referring to Fig. 10 of that patent, memory 252 would have the capability of storing several fingerprint images and bar codes which will be described. In addition, the scanner of that patent would be adapted for battery operation. In a typical law enforcement situation, the scanner is carried by the law enforcement officer, such as in a pouch on his belt, to wherever the subject(s) to be fingerprinted is located. The officer can set the scanner on a suitable supporting surface, such as the hood of an automobile, and then use the scanner to take as many fingerprint images as needed. The subject's finger is placed on the image area 16 and the fingerprint is scanned to develop an image thereof as explained in the above-referenced Patent No. 5,647,364. The images are stored in the scanner 12 for later retrieval. A magnetic base 18 on the scanner facilitates temporary securement of the scanner on the vehicle body during use. The scanner 12 can be provided with bar code scanning capability via a bar code scanner 20 on the end of housing 22 so that when the officer takes a fingerprint image of a subject he also can scan the bar code information on the subject's vehicle registration and/or vehicle operator's license. LED indicators 24, 26 and 28 are provided to signal various scanner conditions as will be described.

An on-off switch 30 controls supply of power to the scanner and hence its operation. Scanner 12 is provided with battery recharging posts 32, 34 on one end of housing 22 which mate with contacts at docking station 14 for recharging the scanner battery in a manner which will be described. Scanner 12 also is provided with an infrared data link 36 for wireless transmission of fingerprint images while stored in docking station 14 as will be described.

The docking station 14 is in the form of a receptacle into which the scanner is inserted after obtaining one or more images. As shown in Fig. 1, the docking station is generally hollow rectangular in shape, open at one end, and having an interior region 40 shaped and sized to receive the scanner in a snug but removable manner. While the scanner is operatively received in the docking station 14, the image(s) stored in the scanner are downloaded via a connection to a personal computer or the like, the scanner battery is recharged and the docking station performs various diagnostic operations on the scanner before it is withdrawn from the docking station for further use. In a typical law enforcement situation, the docking station 14 is located within the law enforcement vehicle, being mounted to the floor or inside wall of the vehicle, such as by the brackets 42, 44 or the like and the scanner 12 can be used by law enforcement personnel at locations remote from the vehicle as previously described. When the law enforcement officer returns to the vehicle, he inserts the scanner 12 in the docking station 14. The scanner 12 is retained within the docking station by a magnetic latch or other suitable means (not shown). The docking station 14 is connected to a source of 12 volts d.c. in the vehicle, such as to the vehicle battery by

appropriate connection or through the cigarette lighter receptacle. The docking station 14 also is connected to the personal computer commonly provided in law enforcement vehicles, via the USB connection 46

5 indicated in Fig. 1. Docking station 14 also is provided with LED status indicators 50, 52 and 54.

While the scanner 12 is in the docking station 14, the images stored therein are downloaded to the onboard PC for processing. The scanner battery is recharged while
10 in the docking station 14. The two battery charging posts 32, 34 shown in Fig. 1 on one end of the scanner 12 mate with corresponding contacts in the docking station 14 to connect the 12V vehicle supply to the scanner battery. Also, each time the scanner 12 is
15 stored in the docking station 14, a diagnostic routine is run on the scanner. If a problem is detected, the next time the scanner 12 is removed from the docking station 14 the scanner automatically is disabled and the appropriate LED status indicator is operated.

20 Table 1 sets forth additional features of scanner 12 and docking station 14, and Table 2 sets forth various advantages of the same.

25 Table 1

Scanner

- Image Size - 0.75"w x 1.0"l
- Stores up to 8 complete fingerprint images
- LED Indicators:
30 Green - scanner ready to acquire image
Amber - flashes the number of fingerprint images stored internally
Red - low battery indicator
- Resolution - 500 dpi, 256 levels of grey

- Infrared wireless communication link downloads images to docking station
- Standard 9 volt rechargeable battery provides several hours of operation
- 5 • Size: 5.75"l x 3.25"w x 2.0"h
- Weight 2.1 lbs

Docking Station

- 12 volt DC operation
- 10 • Interfaces to Mobile Data Terminal via USB port
- LED indicators
 - Green - power on
 - Amber - transferring data to MDT
 - 15 Red - scanner batter recharging
- Built-in 9 volt battery charger
- Floor or side wall mount options
- Complete Software device drivers provided as a DLL for Win 95/98 and NT
- 20 • Size: 9"l x 3.8"w x 2.6"d
- Weight 1.7 lbs

General

- UL 1950, CSA No. 950-22.2, and FCC approvals
- 25 • Reliability - vibration tested to 9.5Gs, 20-2000Hz, random sinusoidal
- Operating Temperature - 140°F (max)
- Storage Temperature - 158°F (max)

30 Table 2

- Proprietary ultrasonic technology unaffected by most contamination found on fingers or platen

- Stores up to 8 individual fingerprints for transferring to Mobile Data Terminal
- Operation unaffected by ambient light or glare
- Self-test scanner diagnostics automatically activated upon removal from the docking station
- Images automatically deleted upon successful transfer to docking station
- Magnetic base easily attached to vehicle
- Durable scratch resistant platen
- Rugged construction designed to withstand the harshest of environments
- Stores in pouch for easy mounting on the law enforcement officer's belt
- Securely locks into docking station
- Vehicle docking station installs easily using floor or side mount bracket

The foregoing is illustrated further in Fig. 2.

The bidirectional arrow 40 represents the path along which scanner 12 is inserted into and withdrawn from interior region 40 of docking station 14. Contacts 62 and 64 within scanner 14 are connected to a battery 66 or other appropriate voltage source for recharging the battery within scanner 12 when scanner contacts 32, 34 mate with docking station contacts 62 and 64. A personal computer 70, i.e., the onboard PC previously mentioned, is connected via cable 72 to the USB connection 46 on docking station 14 for downloading the fingerprint images stored in scanner 12 for processing by computer 70. Another connection via cable 76 between computer 70 and station 14 is shown in Fig. 2 for the purpose of performing the diagnostic routines on scanner 12 as previously described. The LED indicators 50, 52

and 54 are connected by lines 80, 82 and 84 respectively to an appropriate routing/processing circuit 86 which, in turn, is connected by cable 88 to computer 70 for control of the indicators. Obviously, the three cables 72, 76 and 88 shown in Fig. 2 can be combined into a single cable connection between PC 70 and station 14.

Fig. 3 illustrates application of the mobile or portable fingerprint scanner and docking station of the present invention in a security system. In a typical security situation, a single scanner 12' is carried by the security officer and a docking station is located at each checkpoint or location where the officer is to perform an inspection.

In Fig. 3 the three locations identified #1, #2 and #3 represent checkpoints or location where the security guard is scheduled to inspect or contact during his inspection round. While three locations are shown in Fig. 3 by way of illustration, there can be any number of such locations. A docking station of the type shown in Fig. 1 is located at each location #1, #2 and #3 in Fig. 3. They are designated 14', 14" and 14" in Fig. 3. However, each docking station is a stand alone unit, not connected to a PC, and has its own power supply. A microprocessor is provided in each docking station and each station has its own unique identification number or code. The microprocessors are designated 100, 102 and 104 in Fig. 3. Each scanner is provided with a time of day clock, for example clock 110 in scanner 12', and bi-directional communication represented by arrows 112 in Fig. 3 is provided between each scanner and the docking station when the scanner is placed in the station.

When the security officer makes his round, when he reaches each of the locations #1, #2 and #3 shown in Fig. 3, he operates the scanner carried with him to scan

his fingerprint then inserts the scanner into the docking station at that location. The bi-directional communication between scanner and docking station provides a record of the time of day, the unique i.d. of the docking station and the fingerprint image of the security officer. This record can be stored in either or both of the scanner and docking station. Then, when the security officer completes the round, he inserts his scanner into the supervision base or docking station which downloads the fingerprint images along with the times of day correlated with the docking station identification numbers to the PC for further processing such as sending to a central monitoring station. As a result, control is provided on the security officer himself by way of the fingerprint imaging and his round by way of the times of day recorded against the docking station identifications. If desired, the docking stations can be connected together for direct transmission to the PC or other monitor as indicated by the broken lines in Fig. 3.

The principles of the arrangement of Fig. 3 can be applied to other situations, for example in monitoring the rounds of persons who inspect and service ATM machines. In all of the situations, the entire monitoring task can be accomplished using a single scanner in combination with a number of docking stations. Since the docking stations are relatively less expensive to manufacture this can result in economic advantages. In the application illustrated in Figs. 1 and 2, an entire fleet of law enforcement vehicles can be equipped with docking stations at relatively low cost and the fingerprint scanners can be acquired according to operational plans and budget.

5

The Claims

1. A fingerprint identification system comprising:
- 5 a) a portable fingerprint scanner which can be hand carried to various locations for obtaining fingerprint images and for storing the images obtained in the scanner; and
- 10 b) at least one docking station at a location spaced from the location where fingerprint images are obtained, the docking station being in the form of a receptacle for receiving the scanner, the fingerprint images being downloaded from the scanner when the scanner is received in the docking system.
- 15 2. A system according to claim 1, further including a computer operatively connected to the docking station for processing fingerprint images downloaded from the scanner.
- 20 3. A system according to claim 2, wherein diagnostic routines are provided by the computer for operation on the scanner while in the docking station.
- 25 4. A system according to claim 1, wherein the scanner is battery operated and wherein the docking station is provided with a voltage source for recharging the scanner battery when in the docking station.
- 30 5. A system according to claim 1, wherein the scanner is an ultrasonic fingerprint scanner.
6. A system according to claim 1, wherein the scanner has barcode scanning capability.

7. A system according to claim 1, wherein the docking station is located in a law enforcement vehicle and wherein the scanner is adapted to be carried by a law enforcement officer.

5

8. A system according to claim 7, wherein the scanner is provided with an external magnetic component for attachment to a vehicle during use in obtaining images.

10

9. A system according to claim 1, wherein the scanner has an infrared data link for wireless transmission of fingerprint images while received in the docking station.

15

10. A fingerprint identification and security system comprising:

20

a) a portable fingerprint scanner which can be carried on a person and which includes a time of day clock and a port for data communication to and from the scanner;

25

b) a plurality of docking stations at locations where inspections are to be performed, each of the docking stations being in the form of a receptacle for receiving the scanner, each docking station having a microprocessor and a unique code identification, there being bidirectional data communication between the docking station and the scanner received therein; and

30

c) a supervisory docking station in the form of a receptacle for receiving the scanner for downloading fingerprint images, times of day and docking station identifications from the scanner received therein; and

d) whereby when a security person makes a round
when he reaches each inspection location he
operates the scanner to image his fingerprint
and then inserts the scanner into the docking
station at that location and a record is made
of the time of day, unique identification of
the docking station and fingerprint image of
the security person which is stored in the
scanner and then at the end of the round the
security person inserts the scanner into the
supervisory docking station which downloads
the fingerprint images and times of day
correlated with the docking station
identification codes.

11. A system according to claim 10, further included a
computer operatively associated with the supervisory
docking station for processing the downloaded
fingerprint images, times of day and docking station
identification codes.

Abstract

5 A system including a mobile or portable fingerprint scanner and one or more docking stations adapted to
operatively receive the scanner. The scanner can be
hand carried to various locations for obtaining
fingerprint images and other information such as images
from bar code scanning. The scanner is battery operated
and has the capacity of storing a number of such images.
10 The docking station is in the form of a receptacle into
which the scanner is inserted after obtaining one or
more images. While the scanner is operatively received
in the docking station, the image(s) stored in the
scanner are downloaded via a connection to a personal
15 computer or the like, the scanner battery is recharged
and the docking station performs various diagnostic
operations on the scanner before it is withdrawn from
the docking station for further use. In a typical law
enforcement situation, the docking station is located
20 within the law enforcement vehicle and the scanner can
be used by law enforcement personnel at locations remote
from the vehicle. In a typical security situation, a
single scanner is carried by the security officer and a
docking station is located at each checkpoint or
25 location where the officer is to perform an inspection.
Each bay station has a unique identification and there
is bidirectional exchange of information between the
scanner and the bay station so that the identity of the
security officer can be confirmed and a record of the
30 inspections is made which can be monitored at any time.




FIG 2




Fig. 3